

GENERAL PURPOSE FILAMENT TAPE



DESCRIPTION

A strong filament tape consisting of glass filaments laminated to polypropylene film and coated with an aggressive high tack adhesive. It is water and moisture resistant.

MAIN FEATURES

- Strength.
- Water resistant.
- High tack.
- Excellent shear value.
- Little stretch.

APPLICATIONS

- To hold pharmacy cabinet frame together.
- For reinforcing baker's trays.
- As a bond breaker in the concrete industry.
- Palletizing of boxes.
- Strapping rods, moulding, tubes plywood without danger of scratching, staining or damaging.
- Reinforcing boxes, protecting contents from pilferage.

STRENGTH

HIGH TACK

TECHNICAL DATA

Colour	Translucent Ivory
Backing	Polypropylene film laminated to fiberglass filament
Adhesive.....	Thermoplastic rubber
Thickness	4.5 mil
Adhesion	90 oz/in
Tensile Strength.....	110 lb/in
Elongation	6%
Temperature Resistance	-30°C to 55°C (-22°F to 130°F)

STOCK SIZE

9mm x 55m	36mm x 55m
12mm x 55m	48mm x 55m
18mm x 55m	72mm x 55m
24mm x 55m	

Please note:

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.