



OVER SURFACE SPACING
(CREEP DISTANCE) = 3.25"

AVAILABLE THREADS

UNC THREAD STYLES

| PART NUMBER | INSERT SIZE | MATERIAL |
|-------------|---------------|----------|
| 3213-A5 | 3/8-16 X 9/16 | ALUMINUM |
| 3213-S5 | 3/8-16 X 9/16 | STEEL |
| 3213-A6 | 1/2-13 X 5/8 | ALUMINUM |
| 3213-S6 | 1/2-13 X 5/8 | STEEL |
| 3213-A8 | 5/8-11 X 3/4 | ALUMINUM |
| 3213-S8 | 5/8-11 X 3/4 | STEEL |

METRIC THREAD STYLES

| | | |
|-------------|-------------------|----------|
| 3213-A5/M10 | M10 X 1.50 X 14.2 | ALUMINUM |
| 3213-S5/M10 | M10 X 1.50 X 14.2 | STEEL |
| 3213-A6/M12 | M12 X 1.75 X 15.8 | ALUMINUM |
| 3213-S6/M12 | M12 X 1.75 X 15.8 | STEEL |
| 3213-A8/M16 | M16 X 2.00 X 19.0 | ALUMINUM |
| 3213-S8/M16 | M16 X 2.00 X 19.0 | STEEL |

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



MAR-BAL, Incorporated
5400 Reserve Way
Dublin, VA 24084
www.mar-bal.com

| | |
|---|---|
| TITLE 3000 SERIES ROUND INSULATOR | |
| PART NUMBER: 3213-XX | SUGGESTED INDOOR RATING: 2.5 kV |
| SHEET 1 OF 1 | SCALE 1.000 |