



OVER SURFACE SPACING  
(CREEP DISTANCE) = 1.50"

**AVAILABLE THREADS**

**UNC THREAD STYLES**

PART NUMBER	INSERT SIZE	MATERIAL
R2137-A3	5/16-18 X 3/8	ALUMINUM
R2137-S3	5/16-18 X 3/8	STEEL
R2137-A4	3/8-16 X 3/8	ALUMINUM
R2137-S4	3/8-16 X 3/8	STEEL
2138-A4	3/8-16 X 3/8	ALUMINUM

**METRIC THREAD STYLES**

R2137-A3/M8	M8 X 1.25 X 9.5	ALUMINUM
R2137-S3/M8	M8 X 1.25 X 9.5	STEEL
R2137-A4/M10	M10 X 1.50 X 9.5	ALUMINUM
R2137-S4/M10	M10 X 1.50 X 9.5	STEEL

BRASS INSERTS AND OTHER INSERT SIZES AND COMBINATIONS ARE AVAILABLE UPON SPECIAL REQUEST

CONFIDENTIAL  
This print and the specifications are the property of Mar-Bal Inc. and has been issued with the understanding that it will not be reproduced, revealed to or used for manufacture for others, and will be returned upon request.

DATE: 06-AUG-2008



MAR-BAL, Incorporated  
5400 Reserve Way  
Dublin, VA 24084  
www.mar-bal.com

TITLE <b>2000 SERIES ROUND INSULATOR</b>	
PART NUMBER: <b>R2137-XX</b>	UL RATING: <b>600 V</b>
SHEET 1 OF 1	SCALE 1.000